

TECHNICAL INFORMATION

Nº785 Blue Painter's **UV Masking Tape**



PRODUCT DESCRIPTION

No. 785 Blue Painter's UV Masking Tape is a UV resistant blue crepe paper tape. Used predominantly by painters to create sharp lines with no paint bleeding. Trouble-free removal in normal to hot weather conditions.

APPLICATION INFORMATION

- No. 785 is a specialised adhesive masking tape mainly used in painting applications.
- · Ideal for use on painted surfaces and due to it's low-tack adhesive it is easy to remove and does not cause damage to surface when removed. When applied firmly it provides sharp lines and no paint leakage.
- Provides UV resistance for up to 14 days and is suitable for application in hot conditions of up to 100°C.
- · Hand tearable for ease of use.

(4)

PHYSICAL PROPERTIES

Total Thickness 135um Elongation 105% > 28N/25mm Adhesion to Steel **Tensile Strength** 9N/25mm

Adhesive Type Water-based Acrylic Adhesive

AVAILABLE SIZES & COLOURS

* Tolerances: Thickness +/- 2um; Width +/- 1mm

ORDERING CODE	VENUS CODE	DESCRIPTION	WIDTH	METERAGE	THICKNESS	COLOUR	ROLLS /SLEEVE	ROLLS/CARTON	CARTONS/PALLET
A5065024	No.785	UV Masking tape Blue Painters (80-100c)	24mm	50m	135mic	Blue	6	72	96
A5065048	No.785	UV Masking tape Blue Painters (80-100c)	48mm	50m	135mic	Blue	6	36	96



STORAGE & TEMPERATURE CONDITIONS

Storage Tape performance is guaranteed within the first 12 months. Product must be kept in

its original box and in a dry atmosphere away from direct sunlight.

Storage Temp 5°C - 28°C **Application Temp** 0°C - 100°C

Note: The following technical information and data should be considered representative or typical only.

