

TECHNICAL INFORMATION

# Nº600PA PP Printed Tape





#### PRODUCT DESCRIPTION

No 600PA Printed PP tape is a BOPP Printed Tape with a pressure-sensitive water based acrylic adhesive. Used to provide messaging on cartons, parcels and general freight such as 'Fragile', 'This Way Up' etc., to assist with safe passage through supply chain. Message printed black on fluorescent orange or red on white. Comes in 48mm width rolls, 66 metre lengths.

## **/**

## **APPLICATION INFORMATION**

- General packaging, and sealing of cardboard cartons. Suitable for use in benchtop dispensers and hand dispensers.
- For use in applications where moderate to strong adhesion and good initial tack is required such as packing, logistics and warehouse settings.
- Suitable for use in extreme temperatures both high and low, including cold storage.
- Provides superior adhesion to plastic, paper and films.

## [<del>4</del>]

## PHYSICAL PROPERTIES

Total Thickness 50um
Film Thickness 28um
Tensile Strength 75N/25mm

Adhesive Type

Pressure Sensitive

Water-based acrylic

Elongation 120%



## **AVAILABLE SIZES & COLOURS**

\* Tolerances: Thickness +/- 2um; Width +/- 1mm

| DESCRIPTION        | WIDTH | METERAGE | THICKNESS | COLOUR          | ROLLS / SLEEVE | ROLLS / CARTON | CARTONS / PALLET |
|--------------------|-------|----------|-----------|-----------------|----------------|----------------|------------------|
| "Fragile"          | 48mm  | 66m      | 50mic     | Black on orange | 6              | 36             | 60               |
| "Security Seal"    | 48mm  | 66m      | 50mic     | Red on white    | 6              | 36             | 60               |
| "Top Loading"      | 48mm  | 66m      | 50mic     | Black on orange | 6              | 36             | 60               |
| "Handle with care" | 48mm  | 66m      | 50mic     | Black on orange | 6              | 36             | 60               |
| "This way up"      | 48mm  | 66m      | 50mic     | Black on orange | 6              | 36             | 60               |



## STORAGE & TEMPERATURE CONDITIONS

Storage Tape performance is guaranteed within the first 12 months. Product must be kept in

its original box and in a dry atmosphere away from direct sunlight.

**Storage Temp** 5°C – 50°C **Application Temp** 5°C – 60°C

Note: The following technical information and data should be considered representative or typical only.

