

N°122 Cross Weave Filament Tape



PRODUCT DESCRIPTION

No. 122 is a bi-directional filament tape, with a PET film backing and glass fiber reinforcement. Its high tensile strength offers bi-directional reinforcement. It is suitable for multiple application scenarios that demand high tensile strength, durability, and resilience.



APPLICATION INFORMATION

- General bundling and reinforcement, heavy box closure, splicing, sealing edges of special woven bag sealing edge, metal coil closure, pipeline bundling, and more.
- Unparalleled wear resistance.
- Well-suited for applications where resistance to impacts or shocks is essential.
- High holding power.
- Suitable to use in extreme temperatures both high and low.



PHYSICAL PROPERTIES

Total Thickness	120 µm	Adhesive Type	Synthetic Rubber
Tensile Strength	500N/25mm	Elongation	3%
Colour	Clear	Peeling Adhesion	23N/25mm



AVAILABLE SIZES & COLOURS

* Tolerances: Thickness +/- 2µm; Width +/- 1mm

ORDERING CODE	VENUS CODE	DESCRIPTION	PAPER CORE	WIDTH	LENGTH	ROLLS / CARTON	CARTONS / PALLET	ROLLS / PALLET
A6024512	No.122	Cross Weave Filament Tape	76mm	12mm	45m	72	144	10 368
A6024519	No.122	Cross Weave Filament Tape	76mm	19mm	45m	48	144	6 912
A6024525	No.122	Cross Weave Filament Tape	76mm	25mm	45m	36	144	5 184
A6024538	No.122	Cross Weave Filament Tape	76mm	38mm	45m	24	144	3 456
A6024550	No.122	Cross Weave Filament Tape	76mm	50mm	45m	18	144	2 592



STORAGE & TEMPERATURE CONDITIONS

Storage	Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.
Service Temp	-5°C – 70°C

Note: The following technical information and data should be considered representative or typical only.