

TECHNICAL INFORMATION

Nº795 Washi Masking Tape UV (120°C)

PRODUCT DESCRIPTION

No. 795 Washi Masking Tape is a UV resistant green coloured tape with up to 30 days UV resistance. Made from washi paper with an eco water-based adhesive.

APPLICATION INFORMATION

- No. 795 is a premium grade masking tape that offers clean edges and no bleed through.
- Easily removed and leaves no residue.
- Often used in the automotive industry when painting and baking coloured metal. No 795 can withstand high temperatures of up to 120°C. Can be broadly used for protecting objects from dust, overspray and general damage.
- Washi tape can be reapplied multiple times without losing adhesive capabilities. No 795's acrylic adhesive enhances its UV resistance properties.

PHYSICAL PROPERTIES

Total Thickness	105um	Adhesive Type	Water-based Acrylic Adhesive
180° Peeling Adhesion	1.5N/25mm	Elongation	102%
Tensile Strength	30N/25mm	UV Resistance	Up to 30 days

AVAILABLE	AVAILABLE SIZES & COLOURS		es: Thickness +/- 5um; Width +/- 1mm
Standard Width Core Size Standard Length Colours	36mm 76mm (3 inch) 50m Green	Rolls / Sleeve Rolls / Carton Cartons / Pallet	6 48 96

Other sizes available upon request.

STORAGE & TEMPERATURE CONDITIONS

Storage	Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.
Storage Temp	5°C to 28°C
Application Temp	Up to 120°C

Note: The following technical information and data should be considered representative or typical only.

