

TECHNICAL INFORMATION

Nº795 Washi Masking Tape UV (120°C)



PRODUCT DESCRIPTION

No. 795 Washi Masking Tape is a UV resistant green coloured tape with up to 30 days UV resistance. Made from washi paper with an eco water-based adhesive.

/

APPLICATION INFORMATION

- No. 795 is a premium grade masking tape that offers clean edges and no bleed through.
- Easily removed and leaves no residue.
- Often used in the automotive industry when painting and baking coloured metal. No 795 can withstand high temperatures of up to 120°C. Can be broadly used for protecting objects from dust, overspray and general damage.
- Washi tape can be reapplied multiple times without losing adhesive capabilities. No 795's acrylic adhesive enhances its UV resistance properties.

(4)

PHYSICAL PROPERTIES

Total Thickness105umAdhesive TypeWater-based Acrylic Adhesive180° Peeling Adhesion1.5N/25mmElongation102%Tensile Strength30N/25mmUV ResistanceUp to 30 days

E

AVAILABLE SIZES & COLOURS

* Tolerances: Thickness +/- 5um; Width +/- 1mm

Core Size	76mm (3 inch)	Available widths	
Standard Length	50m	9mm x 50m	36mm x 50m
Colours	Green		
Rolls / Sleeve	6	18mm x 50m	48mm x 50m
Rolls / Carton	48		
Cartons / Pallet	96	24mm x 50m	

Other sizes available upon request.



STORAGE & TEMPERATURE CONDITIONS

Storage Tape performance is guaranteed within the first 12 months. Product must be kept in

its original box and in a dry atmosphere away from direct sunlight.

Storage Temp 5°C to 28°C **Application Temp** Up to 120°C

Note: The following technical information and data should be considered representative or typical only.



(03) 9428 1652 🖾 venus@venuspack.com.au 🔗 www.venuspack.com.au