

M1580



PRODUCT DESCRIPTION



For automatic wrapping, simply choose an Up/Down or Up Only cycle then specify the reinforcing wraps as required at the top or bottom or both. Adjust the film carriage speed and the turntable speed then press the start button.

For manual wrapping, there is push button turntable control. Each press of the film carriage button alternatively raises or lowers the film carriage.



PRODUCT FEATURES

- · Gentle, slow stop and start
- Turntable always stops at same home position
- Photo electric eye senses pallet height in auto mode
- Control panel rotates 180 degrees; allows operation from either side
- Film tension adjustment
- Safety trip switch stops film carriage descent if it meets an obstruction
- Servicing and spare parts available.
- Also available optional loading ramp



MACHINE SPECIFICATIONS

Note: The following technical information and data should be considered representative or typical only.

Machine weight 400kg

Machine size (LxWxH) 2325mm x 1500mm x 2345mm

Turntable speed 12rpm
Wrapping height max 2000mm
Turntable Belt driven
Film roll diameter max 250mm
Film width 500mm
Film core diameter 76mm

Pallet load max 1650kg

Power supply 240V single phase Film carriage Chain driven



📞 (03) 9428 1652 🛮 venus@venuspack.com.au 🙋 www.venuspack.com.au